


# condato

# MINI


**LOAD CAPACITY 500 KG**







Condato Mini is our smallest and most cost effective lift. Mini with its compact platform size 700x1100 is suitable for small areas, either as built in or stand alone. It's maximum travel height is 15 meters and it has a load capacity of 500 kg. Mini can cover the needs for most 2-4 floor buildings where space is an issue.

## PLATFORM SIZE



**700 x 1100 mm**



|  |   |   |   |                        |
|--|---|---|---|------------------------|
| <b>RECOMMENDED INSTALLATION</b><br>Indoors and outdoors  | <br><b>DRIVE SYSTEM</b><br>Screw and nut | <b>PLATFORM BUTTONS</b><br>Automatic Run<br>All buttons with tactile and braille  | <b>BATTERY EMERGENCY LOWERING</b><br>incl. as standard  | <b>MOTOR</b><br>2.2 kW |
| <br><b>RATED LOAD</b>   500 kg  | <b>CONTROL SYSTEM</b>   PLC   | <b>CERTIFICATION</b>   MD 2006 / 42 / EC  | <b>PIT DEPTH</b>   50 mm  |                        |
| <b>HEIGHT LIMITS</b><br>Max travel height 15 m<br>Top height 2.3 m   | <br><b>DOOR BUTTONS</b><br>One touch     | <br><b>STANDARD EPS PANEL</b><br><br><b>RATED SPEED</b>   Max 0.15 m/sec | <br><b>POWER SUPPLY</b><br>230/380 V 1/3-phase 50/60 Hz 16A, frequency converter |                        |
| <b>STOPS</b><br>Max 5 stops<br> | <b>MANUFACTURED IN SWEDEN</b>   |   |   |                        |

Mobile: +46 8 5592 1358  
 Email: support@condatogroup.com  
 Website: www.condatogroup.com

Condato Group - Box 282, 177 25 Järfälla, Sweden

# OPTIONS



- Shaft Panels Color
- Corner Profile Color
- Door Handle Color  
Stainless steel
- Glass Frame Color
- Automatic Door Opener
- Level Indicator
- Door Frame Color
- Door Blade Color
- Key Control with Buttons  
To lock the calling button for prevent unauthorized person use.
- Door Window Frame Color

**Automatic Door Opener (optional)**




**Door Handle, 30 cm**  
Black painted (standard)  
Stainless steel (optional)



**Ramp (optional)**

If the lift is installed without a pit, a ramp is required according to the EN81.41.



**Level Indicator (optional)**

Digital display that indicates which floor the lift is currently standing on.



**2-Way Communication System (optional)**

All Condato lifts except Condato Mini are able to install a 2-way communication system which allows access from inside and outside the lift in case of emergency.



**Half Door - Top Floor (optional)**

## LIFT CARPET COLOR

Standard



0702

(Black Rubber)

Option 1



6172

(Choose between 20 different colors)

2



0733

3



6173

## LIFT COLOR




Standard  
RAL 9003

**optional**



5014



8022



1036



7011



6034



7003



3004



10011



**High Back Platform (optional)**