







condato

PRIME

LOAD CAPACITY 500 KG

Condato Prime lift is blending of classic design with simplicity. Made with passion for safety and functionality. Prime offers platform sizes from 1100- 1600 mm, a travel height of 15 meters and a solid load capacity of 500 kg.



RECOMMENDED INSTALLATION Indoors and outdoors	 DRIVE SYSTEM Screw and nut	PLATFORM BUTTONS Automatic Run All buttons with tactile and braille	BATTERY EMERGENCY LOWERING incl. as standard	MOTOR 2.2 kW
 RATED LOAD 500 kg	CONTROL SYSTEM PLC	CERTIFICATION MD 2006 / 42 / EC	PIT DEPTH 50 mm	
HEIGHT LIMITS Max travel height 15 m Top height 2.3 m	 DOOR BUTTONS One touch	 STANDARD EPS PANEL RATED SPEED Max 0.15 m/sec	 POWER SUPPLY 230/380 V 1/3-phase 50/60 Hz 16A, frequency converter	
STOPS Max 5 stops 	MANUFACTURED IN SWEDEN			

Mobile: +46 8 5592 1358
 Email: support@condatogroup.com
 Website: www.condatogroup.com

Condato Group - Box 282, 177 25 Järfälla, Sweden



OPTIONS



Automatic Door Opener (optional)




Door Handle, 30 cm
Black painted (standard)
Stainless steel (optional)



Ramp (optional)

If the lift is installed without a pit, a ramp is required according to the EN81.41.



Level Indicator (optional)

Digital display that indicates which floor the lift is currently standing on.



2-Way Communication System (optional)

All Condato lifts except Condato Mini are able to install a 2-way communication system which allows access from inside and outside the lift in case of emergency.



Half Door - Top Floor (optional)

LIFT CARPET COLOR

Standard



0702

(Black Rubber)

Option 1



6172

(Choose between 20 different colors)

2



0733

3



6173

LIFT COLOR




Standard
RAL 9003

optional



5014



8022



1036



7011



6034



7003



3004



10011



High Back Platform (optional)